



ISO 9001:2000 REGISTERED

VCL Plow Harness Systems

500T Hydraulic Tilt Harness

Viking power tilt plow harness meets all MTO specifications. Bolted to the truck frame with cheekplates. Lift ram is 4" x 10" DA. Tilt cylinder 2 1/2 x 6" DA. New design allows free flow of air to truck engine. Tilt works on 4" tube hinge, no pins to wear.



500LT Hydraulic Lift & Tilt Harness

Viking power tilt plow harness with lighter tubular steel frame. This puts less weight on the truck front axle. Lift/tilt ram is 4" x 10" DA.



500F Fixed Place/Mount Harness

Viking fixed in place plow harness. No tilt feature.



500LM Low Mount Harness

Viking low mount plow harness bolts to the truck frame as well as cheekplates to frame. Great weight reduction and no restriction of air to truck radiator. Lift ram 4" x 10" DA. For use with plow mount only.

**Viking low mount has been modified to suit the Alberta market. (photo on right)*



500HD Hydraulic Detach & Tilt Harness

Viking hydraulic detach plow harness has all features of the tilt harness plus allowing for hydraulic detach of plow harness and side wing as a single unit. Lift ram is 4" x 10" DA. Tilt ram is 2 1/2 x 6" DA. Hydraulic lock and 2 double end cylinders releasing top pin only allows for tilt feature. With the detachable feature there is less weight on truck front axle.

**500MD is the same as 500HD plow harness except with manual lock pins.*



All Viking plow harnesses have drive locations which can be set to your requirements. All harnesses accept quick tack pockets and pins, as well as other quick attach devices.

April 21, 2009



Viking-Cives (USA)
14331 Mill Street
Harrisville, NY 13648
315-543-2321 Phone
315-543-2366 Fax

Viking-Cives Ltd.
P.O. Box 1120 RR#4
Mount Forest, ON N0G 2L0
519-323-4433 Phone
519-323-4608 Fax

Viking-Cives Midwest
P.O. Box 295 22956 Hwy 61
Morley, MO 63767
573-262-3545 Phone
573-262-3540 Fax