



Viking Proline HW Series

ISO 9001:2000 REGISTERED



Model	Inside Overall Length	Outside Overall Length	Install Weight (approx)	Water Level Capacity	10" Boards (optional)	Front Panel Height	Side Height	Tailgate Height	Hoist	Conveyor Width
PL1011HW	10'	11'	6,100 lbs	8 yd3	10 yd3	52"	45"	53"	TBA	25.75"
PL1213HW	12'	13'	6,800 lbs	12 yd3	12.5 yd3	60"	53"	62"	TBA	25.75"
PL1314HW	13'	14'	7,000 lbs	13 yd3	14.5 yd3	60"	53"	62"	TBA	25.75"
PL1415HW	14'	15'	7,200 lbs	14 yd3	17 yd3	60"	53"	62"	30 ton	25.75"
PL2021HW	20'	21'	8,400 lbs	20 yd3	24.5 yd3	60"	53"	62"	50 ton	25.75"

Standard Features:

- 25:1 Planetary
- AR235 wear plate under chain
- Front discharge
- 3/16" Corten-A steel body construction
- Front LH inspection ladder
- Air tailgate

Options:

- Reversible cross conveyors (chain or rubber)
- Front dual cross conveyor spinner (dual auger)
- High tensile construction
- Box lighting
- Material screens
- Air tarp
- Liquid tanks
- Dupont Imron 5000 Paint
- Asphalt door in tailgate

February 19, 2008



Viking-Cives (USA)
 14331 Mill Street
 Harrisville, NY 13648
 315-543-2321 Phone
 315-543-2366 Fax

Viking-Cives Ltd.
 P.O. Box 1120 RR#4
 Mount Forest, ON N0G 2L0
 519-323-4433 Phone
 519-323-4608 Fax

Viking-Cives Midwest
 P.O. Box 295 22956 Hwy 61
 Morley, MO 63767
 573-262-3545 Phone
 573-262-3540 Fax