



Sidewalk Unloader Conveyor

ISO 9001:2000 REGISTERED



The Viking-Cives Ltd. Sidewalk Unloader Conveyor can be easily attached to your new Proline LW Gen II spreader dump body with reversible belt cross conveyor. This allows material to be discharged into sidewalk spreader hoppers.



Viking-Cives Ltd. Sidewalk Unloader Conveyor folds tight to side of dump body for storage and transport.

Specifications

Conveyor Length	60 inches
Conveyor Width	12 inch belt width, 16 1/2 inch overall
Belt	Rubber, c/w molded cleat, 1/2 inch thickness
Drive Type	Positive engagement sprocket
Discharge Height	36 inch to 48 inch, varies with chassis height
Construction	Heavy duty 3/16" Cor-ten A side frame belt on roller, no wear strips to replace
Controls	Hydraulic raise/lower conveyor incline adjustment. Variable conveyor speed
Attachment	Pin in place, easily attached or detached quick disconnect hydraulics

March 26, 2008



Viking-Cives (USA)
 14331 Mill Street
 Harrisville, NY 13648
 315-543-2321 Phone
 315-543-2366 Fax

Viking-Cives Ltd.
 P.O. Box 1120 RR#4
 Mount Forest, ON N0G 2L0
 519-323-4433 Phone
 519-323-4608 Fax

Viking-Cives Midwest
 P.O. Box 295 22956 Hwy 61
 Morley, MO 63767
 573-262-3545 Phone
 573-262-3540 Fax